

[FA] Módulos para riel

HDR-60-24V 2.5A



- [Aliexpress](#)
- Especificaciones
- Instalación

HDR-60-24V 2.5A

The image shows a black HDR-60-24V 2.5A module. The front panel features a terminal block with four terminals labeled -V, +V, +V, and -V. Below the terminals, there is a potentiometer labeled 'V_o Adj.' and a warning 'Terminal torque 3.0 Lb-in'. The model number 'HDR-60-24' is printed in the center. Below it, the input specifications are listed: 'INPUT: 100-240VAC 1.8A 50/60Hz'. The output specifications are listed below that: 'OUTPUT: 24V --- 2.5A'. The CE and RoHS logos are printed at the bottom of the front panel. The bottom of the module has two terminals labeled 'L' and 'N' with a warning 'Terminal torque 3.0 Lb-in'. The dimensions are indicated as 52.5mm width, 54.5mm depth, and 90mm height.

Model	HDR-60-24	Power	60W
Output voltage	24V	Input voltage	100-264VAC 120-370VDC



Model:		HDR-15---	HDR-30---	HDR-60---	HDR-100---
Input:		85-264VAC		120-370VDC	
Output:	Power:	15W	30W	60W	100W
	DC voltage:	12V / 24V	12V / 24V	12V / 24V	12V / 24V
	Rated current:	1.25A / 0.63V	2A / 1.5A	4.5A / 2.5A	7.A / 2.83A
	Voltage accuracy:	±1.0%	±1.0%	±1.0%	±1.0%
	Line Regulation:	±1.0%	±1.0%	±1.0%	±1.0%
	Load Regulation:	±1.0%	±1.0%	±1.0%	±1.0%
	Start rise time:	500ms, 50ms/230VAC 500ms, 50ms/115VAC (the full load)			
Frequency:	47-63Hz				

From: <https://euloxio.myds.me/dokuwiki/> - Euloxio wiki

Permanent link: https://euloxio.myds.me/dokuwiki/doku.php/doc:tec:elo:lab_fa:modulo:inicio

Last update: 2024/12/04 18:42

